

## SeamGuard™ WB

**COLOR:** White

- BASIC USES:**
- Seals seams and fasteners
  - Caulks

**PRODUCT DESCRIPTION:** SeamGuard™ WB elastomeric sealer is designed specifically for seams and fasteners when Topps Seal® WB is used. Additional polymers with adhesion enhancers allow SeamGuard WB to accept extra duty that sometimes is required at joints, helping keep them sealed. The durable and highly elastic resins can stretch to 750% and recover for more action. Special UV inhibitors promote constant exposure to sun and weather with minimal change.

- FEATURES:**
- Permanently flexible
  - Caulks and seals at the same time
  - Stable to moisture in as little as 4 hours
  - No VOC
  - Compatible with Topps Seal® WB

<b>WET MATERIAL</b> <i>Typical Product Characteristics:</i>	Viscosity	90 - 105 K.U.
	Weight per gallon	9 - 10 lb.
	Solids	37.5 - 40%
	Flashpoint of solvent	N/A
	VOC	0
	pH	>8.5
	Coverage Rate	200-300 linear ft/gal. @ 4" width per coat (2)
<b>CURED COATING</b> <i>Typical Performance Properties:</i>	Dry to touch @ 77° F (50% rel. humidity)	4 hrs
	Ultimate Elongation	750%
	Ultimate tensile strength	300 psi
	Water vapor permeability	17.0 perms
	Reflectivity	>65%
	Thermal Emittance	>0.8