

SkyCoat™

COLORS: Clear

- BASIC USES:**
- Extends service life of skylights
 - Protects fiberglass/polycarbonate skylights
 - Helps prevent chalking, oxidation, weathering

PRODUCT DESCRIPTION: This resin rich formula creates a shield and protective skin that remains pliable. Cures directly to the surface and helps protect against oxidation and chalking. Applies in two coats, each at 1 gallon per square. Dries nearly transparent.

- FEATURES:**
- Permanent flexibility
 - Strong bonding
 - Resists acid rains and other common pollutants
 - Quick moisture resistance in 2-4 hrs

WET MATERIAL <i>Typical Product Characteristics:</i>	Viscosity	105 - 110 K.U.
	Weight per gallon	8.4 - 8.8 lb.
	Solids	58%
	Flashpoint of solvent	104° F
	VOC	<450 g/l
CURED COATING <i>Typical Performance Properties:</i>	Dry to touch @ 77° F (50% rel. humidity)	~ 4 hrs
	Ultimate Elongation	1000% min.
	Ultimate tensile strength	1000 psi min.
	Peel Adhesion	2.4 pli
	Water vapor permeability	0.18 Perms
	Moisture absorption -7 day submersion-	<0.45% max
	Service Temperature	-40° - 140° F