

Topps Seal[®] WB

COLOR: White

- BASIC USES:**
- Protects against water, UV, weather
 - Roof maintenance - exterior wall coating
 - Energy Savings

PRODUCT DESCRIPTION: Elastomeric Topps Seal[®] WB, with enhanced adhesive and flow agents, easily produces an attractive and effective blemish-free new weathering surface for roofs and walls that repels moisture, UV, and weather. The smooth and more even finish assure improved results with any application. Special polymers, blended with pure titanium dioxide, develop the rubber like shield that remains pliable and will not yellow over time. Achieves superior bleed-through and stain blocking too. The high resin content eliminates need for primer, in most circumstances. Applies to bituminous surfaces, metal, masonry, block, and concrete. Cured Topps Seal WB is effective in all climates.

- FEATURES:**
- Permanently flexible
 - Caulks and seals at the same time
 - Excellent weather, pollution, and acid rain resistance
 - Stable to moisture in as little as 4 hours
 - Breathes
 - No VOC
 - ENERGY STAR[®] - CRRC[®] Registered

WET MATERIAL	Viscosity	90 - 105 K.U.
<i>Typical Product Characteristics:</i>	Weight per gallon	11 - 12 lb.
	Solids	57.5 - 60%
	Flashpoint of solvent	N/A
	VOC	0
	pH	>8.5
	Dry to touch @ 77° F (50% rel. humidity)	4 hrs
CURED COATING	Ultimate Elongation	200%
<i>Typical Performance Properties:</i>	Ultimate tensile strength	210 psi
	Perm Rating	17.5 perms
	Reflectivity	86.07%
	Thermal Emittance (initial/aged)	0.87/0.90
	SRI (initial/aged)	108/77
	Service Temperature	-20° - 140° F.

OMTDTSWB142226